

RoughDeck® QUICK CLEAN

STAINLESS STEEL FLOOR SCALE



RICE LAKE®
WEIGHING SYSTEMS

To be the best by every measure™

www.ricelake.com

RoughDeck® **QC** QUICK CLEAN

STAINLESS STEEL FLOOR SCALE



The rugged design incorporates 304 stainless steel construction and four welded-seal load cells with PTFE cable designed for high temperatures and washdown areas.

Known as the toughest, most accurate floor scale line in existence, the RoughDeck's legendary performance is now customized for food, chemical and other frequent washdown applications.

RoughDeck QC is *the* weighing solution for efficiency and safety when cleaning cycles are tight. Our exclusive gas-shock design offers easy lifting, but even more importantly, eliminates dangerous slamming of the deck when closing. For added safety and convenience, a manual support bar swings into action during extended underdeck cleaning.

Legendary RoughDeck performance and innovative specialty features—the ultimate washdown solution.



Dual corner locks secure the deck to the base for safety, durability and convenience.

Unique dual gas-shock design provides easy opening and gentle closing.



Dimensions/Capacities:

PART #	SIZE	CAPACITY LB (KG)	SHIP WT LB
50402	2.5' x 2.5'	2,000 lb (1000 kg)	158 lb
50403	3' x 3'	2,000 lb (1000 kg)	208 lb
50404	4' x 4'	2,000 lb (1000 kg)	338 lb
50405	4' x 4'	5,000 lb (2500 kg)	338 lb
50406	4' x 4'	10,000 lb (5000 kg)	447 lb
50407	4' x 5'	2,000 lb (1000 kg)	406 lb
50408	4' x 5'	5,000 lb (2500 kg)	406 lb
50409	4' x 5'	10,000 lb (5000 kg)	540 lb
50410	4' x 6'	2,000 lb (1000 kg)	477 lb
50411	4' x 6'	5,000 lb (2500 kg)	477 lb
50412	4' x 6'	10,000 lb (5000 kg)	637 lb
50413	5' x 5'	2,000 lb (1000 kg)	478 lb
50414	5' x 5'	5,000 lb (2500 kg)	478 lb
50415	5' x 5'	10,000 lb (5000 kg)	637 lb
50416	5' x 7'	2,000 lb (1000 kg)	705 lb
50417	5' x 7'	5,000 lb (2500 kg)	705 lb
50418	5' x 7'	10,000 lb (5000 kg)	908 lb

Your Rice Lake Weighing Systems distributor is:

Standard Features:

- Rugged washdown design
- Smooth, 304 stainless steel top deck
- Four stainless steel, welded-seal, shear beam load cells
- Rigid 304 stainless steel tube frame
- Remote EL604 stainless steel NEMA 4X junction box
- Four adjustable stainless steel SUREFOOT support feet
- 20 ft of SURVIVOR® hostile environment load cell cable to connect an indicator to the junction box
- Safety bar

Options/Accessories:

- Stainless steel deck with treadplate
- Floor stand for indicator: stainless steel, 36.3" high, and fits IQ plus® 355, IQ plus® 390-DC, IQ plus® 510, IQ plus® 590-DC and IQ plus® 710



Choose from a versatile line of digital weight indicators.



Slip NOT® (optional) state-of-the-art slip-resistant surface is the long-term solution for accident-free performance.



Optional stainless steel treadplate available.

Specifications:

- End Load Capacity:** 100% full scale
- mV/V Output:** 1.50-1.87 mV/V nominal
- Remote J-Box:** Stainless steel NEMA 4X enclosure can be located up to 10 ft away from the scale
- Warranty:** 5-year limited warranty

Approvals:



NTEP CC 92-001A5
 $n_{max} = 5,000$
 Class III

RICE LAKE
 WEIGHING SYSTEMS
 To be the best by every measure®

230 W. Coleman St. • Rice Lake, WI 54868 • USA
 TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com

An ISO Registered Company © 2008 Rice Lake Weighing Systems PN 53373 9/08
 Specifications subject to change without notice